



► INFLATABLES

	310 AERO	310 S	360 S	420 S
DIMENSIONS (METERS - FEET/INCHES)				
Overall length	3,1 - 10'2"	3,1 - 10'2"	3,6 - 11'10"	4,2 - 13'9"
Inside length	1,94 - 6'4"	1,94 - 6'4"	2,33 - 7'8"	2,8 - 9'2"
Overall width	1,62 - 5'4"	1,62 - 5'4"	1,74 - 5'9"	1,9 - 6'3"
Inside width	0,79 - 2'7"	0,79 - 2'7"	0,88 - 2'11"	0,92 - 3'0"
Buoyancy tube diameter	0,42 - 1'5"	0,42 - 1'5"	0,43 - 1'5"	0,49 - 1'7"
CAPACITY				
Passengers (ISO)	4	4	5	7
Maximum payload (kg - lbs)	500 - 1102,3	500 - 1102,3	600 - 1322,8	750 - 1653,5
Total weight ¹ (kg - lbs)	39 - 86,0	45 - 99,2	64 - 141,1	82 - 180,8
Airtight compartments	3+1+1	3+1	3+1	5+1
DESIGN CATEGORY²				
European directive N° 94/25/CE	C	C	C	C
MOTORISATION				
Shaft: ● Short ■ long ✖ Extralong * Ultralong ▲ Jet	●	●	●	●
Average recommended power (in HP)	5	8	15	15
Average recommended power (in kW)	4	6	12	12
Maximum power allowed (Hp)	8	10	20	25
Maximum power allowed (kW)	6	8	15	19
Maximum weight of outboard ³ (kg - lbs)	42 - 92,6	52 - 114,6	52 - 114,6	72 - 158,7
Maximum speed (km/h - mph)	26 - 16	31 - 19	38 - 24	40 - 25
DIMENSIONS OF THE FOLDED BOAT (METERS - FEET/INCHES)				
Length of 1st bag	1,14 - 3'9"	1,15 - 3'9"	1,2 - 3'11"	1,3 - 4'3"
Width of 1st bag	0,6 - 1'12"	0,55 - 1'10"	0,67 - 2'2"	0,75 - 2'6"
Height of 1st bag	0,32 - 1'1"	0,32 - 1'1"	0,3 - 0'12"	0,3 - 0'12"
Length of 2nd bag	-	-	1,12 - 3'8"	1,2 - 3'11"
Width of 2nd bag	-	-	0,77 - 2'6"	0,8 - 2'8"
Height of 2nd bag	-	-	0,15 - 0'6"	0,16 - 0'6"

[1] The weights indicated for the Typhoon, AX, MAX, AX Compact and MAX RIB include the floorboard, paddles/oars and pump.

[2] Applies only for EEC [European directive 94/25/CE].

[3] Maximum authorized weight: Dry weight, according to the engine manufacturers catalogue's specifications.

EQUIPMENT LIST

HULL	BUOYANCY TUBE	STANDARD EQUIPMENT	OPTIONAL EQUIPMENT
<ul style="list-style-type: none"> • Inflatable keel • Non-skid wooden floor + aluminum stringers with tie-down rail (except T 310 AERO) • Removable inflatable floor (T 310 AERO) • Aluminum motor plate • 1 self-bailer 	<ul style="list-style-type: none"> • 1100 decitex fabric • Semi-recessed valves (Bravo type) • Lifeline • Rubbing strake with outlined profile • Fittings for additional bench seat (T 360 S / T 420 S) • 1 bow handle strap • 2 carrying handles (4 for T 360 S/ T 420 S) • 2 towing rings • 2 reclining oar supports • Reinforced cone ends 	<ul style="list-style-type: none"> • 1 carry bag with utility pockets • 2 reinforced aluminum oars • 1 foot pump • 1 repair kit • Owner's manual • Bench seat 	<ul style="list-style-type: none"> • Inflatable thwart (except T 420 S) • Removable bow bag hold-all with Velcro fastening • Bench bag • Overall cover • Bench seat on rails (except T 310 AERO) • Launching wheels • Fishing rod holders • Trim Tabs • Boarding ladder • Electric pump