



► INFLATABLE TENDERS

	230	260 AERO	260 S	310 S	350 S
DIMENSIONS (METRES - FEET/INCHES)					
Overall length	2,3 - 7'7"	2,6 - 8'6"	2,6 - 8'6"	3,1 - 10'2"	3,5 - 11'6"
Inside length	1,44 - 4'9"	1,64 - 5'5"	1,64 - 5'5"	2,08 - 6'10"	2,4 - 6'8"
Overall width	1,34 - 4'5"	1,53 - 5'0"	1,53 - 5'0"	1,55 - 5'1"	1,72 - 5'8"
Inside width	0,62 - 2'0"	0,68 - 2'3"	0,68 - 2'3"	0,68 - 2'3"	0,83 - 2'9"
Buoyancy tube diameter	0,36 - 1'2"	0,43 - 1'5"	0,43 - 1'5"	0,44 - 1'5"	0,45 - 1'6"
CAPACITY					
Passengers (ISO)	2+1	3	3	4	5
Maximum payload ¹ (kg - lbs)	270 - 595,3	400 - 881,9	450 - 992,1	600 - 1322,8	650 - 1433,0
Total weight (kg - lbs)	26 - 57,3	36 - 79,4	40 - 88,2	47 - 103,6	65 - 143,3
Airtight compartments	2	3+1+1	3+1	3+1	3+1
DESIGN CATEGORY					
European directive N° 94/25/CE	-	D	D	C	C
OUTBOARD DATA					
● Short shaft ■ Long shaft	●	●	●	●	●
Minimum recommended power ² (Hp)	3	3	6	10	15
Minimum recommended power ² (kW)	2,3	2,3	4,5	8	12
Maximum recommended power ² (Hp)	4	6	8	15	20
Maximum recommended power ² (kW)	3	4,5	6	12	15
Maximum power allowed ³ (Hp)	4	6	8	15	20
Maximum power allowed ³ (kW)	3	4,5	6	12	15
Maximum weight of outboard ⁴ (kg - lbs)	26 - 57,3	42 - 92,6	42 - 92,6	52 - 114,6	52 - 114,6
Maximum speed ⁵ (km/h - mph)	-	-	-	-	-
DIMENSIONS OF THE FOLDED BOAT (METRES - FEET/INCHES)					
Length of 1st bag	0,99 - 3'3"	1,05 - 3'5"	1,12 - 3'8"	1,1 - 3'7"	1,15 - 3'9"
Width of 1st bag	0,5 - 1'8"	0,56 - 1'10"	0,64 - 2'1"	0,6 - 1'12"	0,55 - 1'10"
Height of 1st bag	0,3 - 0'12"	0,32 - 1'1"	0,3 - 0'12"	0,32 - 1'1"	0,3 - 0'12"
Length of 2nd bag	-	-	-	-	1,12 - 3'8"
Width of 2nd bag	-	-	-	-	0,77 - 2'6"
Height of 2nd bag	-	-	-	-	0,15 - 0'6"

All dimension measurements indicated have a tolerance of +/- 3%. Weight and speed measurements have a tolerance of +/- 5%.

(1) The maximum payload rating has been calculated according to ISO standards. Operating at or near maximum payloads is only advised in calm water and at reduced speeds.

(2) The spread of engine sizes corresponds to the efficient use of the boat with an average load. The minimum power is exploitable in relaxed activities, such as fishing, while the maximum recommended power is destined for performance activities such as water-skiing. For additional information all Zodiac boats from 10'2"/3.10 m to 13'9"/4.20 m can plane with 2 people on board (total load of 310 lbs/140 kg) using only a 6-8 Hp/5-6 kW outboard.

(3) Where the boat is fitted with an engine that exceeds Zodiac's maximum recommended power it must be treated with extreme care. This application is directed at experienced users using their boats for very specific purposes (carrying heavy loads, etc.). The capacity plate shows the maximum allowed power. In no case shall the boat be fitted with an engine that exceeds this power.

(4) Maximum authorized weight: Dry weight, according to engine manufacturers catalogue's specifications. Where the boat is fitted with an engine that exceeds Zodiac's maximum recommended power it must be treated with extreme care. This application is directed at experienced users using their boat for very specific purposes (carrying heavy loads, etc.). The capacity plate shows the maximum allowed power. In no case shall the boat be fitted with an engine that exceeds this power.

(5) Maximum speeds are given only as a general guide to understanding boat performance. They have been established by experienced professional pilots in ideal navigating conditions with one person aboard. Boat speed will be affected by the make of the motor, boat load, propeller and the water and weather conditions.



EQUIPMENT LIST

HULL	BUOYANCY TUBE	STANDARD EQUIPMENT	MAIN OPTIONAL ACCESSORIES
<ul style="list-style-type: none"> • Inflatable keel (except 230) • Slatted wooden floor (230) • Marine plywood floor + 2 aluminium stringers (260 S / 310 S / 350 S) • Removable air floor (260 AERO) • Engine support plate • 1 interior commanded self-bailer 	<ul style="list-style-type: none"> • 1100 decitex material • Semi-recessed valves (Bravo type) • Safety line • 2 oar rests • 2 reclining oar supports • All round ribbed rubbing strake • 1 bow handle • 2 carrying handles • 2 stainless steel towing rings • Fittings for additional bench seat (350 S) • Reinforced cone ends 	<ul style="list-style-type: none"> • Aluminium oars • Wooden bench • Carry bag • Foot pump • H2P foot pump (260 AERO) • Repair kit • Owner's manual 	<ul style="list-style-type: none"> • 12 V electric inflator with pressure control - capacity 0,3 bar/4,35 PSI • Bathing ladder • Launching wheels • Bench bag • Removable bow bag holdall